



SUNNY HIGHPOWER PEAK3 125-US / 150-US

SHP 125-US-20 / SHP 150-US-20



Cost effective

- Modular architecture reduces BOS and maximizes system uptime
- Compact design and high power density maximize transportation and logistical efficiency

Maximum flexibility

- Scalable 1,500 VDC building block with best-in-class performance
- Flexible architecture creates scalability while maximizing land usage

Simple install, commissioning

- Ergonomic handling and simple connections enable quick installation
- Centralized commissioning and control with SMA Data Manager

Highly innovative

- SMA Smart Connected reduces O&M costs and simplifies field-service
- Powered by award winning ennexOS cross sector energy management platform

SUNNY HIGHPOWER PEAK3 125-US / 150-US

A superior modular solution for large-scale power plants

The PEAK3 1,500 VDC inverter offers high power density in a modular architecture that achieves a cost-optimized solution for large-scale PV integrators. With fast, simple installation and commissioning, the Sunny Highpower PEAK3 is accelerating the path to energization. SMA has also brought its field-proven Smart Connected technology to the PEAK3, which simplifies O&M and contributes to lower lifetime service costs. The PEAK3 power plant solution is powered by the ennexOS cross sector energy management platform, 2018 winner of the Intersolar smarter E AWARD.

| Technical Data | Sunny Highpower PEAK3 125-US | Sunny Highpower PEAK3 150-US |
|---|--|------------------------------|
| Input (DC) | | |
| Maximum array power | 187500 Wp STC | 225000 Wp STC |
| Maximum system voltage | 1500 VDC | |
| Rated MPP voltage range | 705 V ... 1450 V | 880 V ... 1450 V |
| MPPT operating voltage range | 684 V ... 1500 V | 855 V ... 1500 V |
| MPP trackers | 1 | |
| Maximum operating input current | 180 A | |
| Maximum input short-circuit current | 325 A | |
| Output (AC) | | |
| Nominal AC power | 125000 W | 150000 W |
| Maximum apparent power | 125000 VA | 150000 VA |
| Output phases / line connections | 3 / 3-PE | |
| Nominal AC voltage | 480 V | 600 V |
| Compatible transformer winding configuration | Wye-grounded | |
| Maximum output current | 151 A | |
| Rated grid frequency | 60 Hz | |
| Grid frequency / range | 50 Hz, 60 Hz / -6 Hz ... +6 Hz | |
| Power factor at rated power / adjustable displacement | 1 / 0.0 leading ... 0.0 lagging | |
| Harmonics (THD) | <3% | |
| Efficiency | | |
| CEC efficiency | 98.5 % | 99.0 % |
| Protection and safety features | | |
| Ground fault monitoring: Riso / Differential current | ● / ● | |
| DC reverse polarity protection | ● | |
| AC short circuit protection | ● | |
| Monitored surge protection (Type 2): DC / AC | ● / ● | |
| Protection class / overvoltage category (as per UL 840) | I / IV | |
| General data | | |
| Device dimensions (W / H / D) | 770 / 830 / 444 mm (30.3 / 32.7 / 17.5 in.) | |
| Device weight | 98 kg (216 lbs) | |
| Operating temperature range | -25°C ... +60°C (-13°F ... +140°F) | |
| Storage temperature range | -40°C ... +70°C (-40°F ... +158°F) | |
| Audible noise emission (full power @ 1m and 25°C) | < 69 dB(A) | |
| Internal consumption at night | < 5 W | |
| Topology | Transformerless | |
| Cooling concept | OptiCool (forced convection, variable speed fans) | |
| Enclosure protection rating | Type 4X (as per UL 50E) | |
| Maximum permissible relative humidity (non-condensing) | 100% | |
| Additional information | | |
| Mounting | Rack mount | |
| DC connection | Terminal lugs - up to 600 kcmil CU/AL | |
| AC connection | Screw terminals - up to 300 kcmil CU/AL | |
| LED indicators (Status/Fault/Communication) | ● | |
| SMA Speedwire (Ethernet network interface) | ● (2 x RJ45 ports) | |
| Data protocols: SMA Modbus / SunSpec Modbus / Webconnect | ● / ● / ● | |
| Integrated Plant Control / Q on Demand 24/7 | ● / ● | |
| Off-grid capable / SMA Hybrid Controller compatible | - / ● | |
| SMA Smart Connected (proactive monitoring and service) | ● | |
| Certifications | | |
| Certifications and approvals | UL 62109, UL 1998, CAN/CSA-C22.2 No.62109 | |
| FCC compliance | FCC Part 15, Class A | |
| Grid interconnection standards | IEEE 1547, UL 1741 SA - CA Rule 21, HECO Rule 14H | |
| Advanced grid support capabilities | L/HVRT, L/HVRT, Volt-VAr, Volt-Watt, Frequency-Watt, Ramp Rate Control, Fixed Power Factor | |
| Warranty | | |
| Standard | 5 years | |
| Optional extensions | 10 / 15 / 20 years | |
| Type designation | SHP 125-US-20 | SHP 150-US-20 |
| Technical data as of April 2019 ● Standard features ○ Optional features – Not available | | |

SHP150-US-16: Changes to products and services, including those resulting from country-specific requirements, as well as deviations from technical data are subject to change at any time without notice. SMA assumes no liability for typographical or other errors. Please visit www.SMA-Solar.com for the latest information.